

1.8M Ka-Band Antenna

Series 3180

Technical Specifications

Electrical		Ka-Band Circular	Ka-Band Circular	Ka-Band Linear
Antenna Size		1.8 M	1.8 M	1.8 M
Operating Frequency (GHz)	Receive	20.20 - 21.20 GHz	19.40 - 21.20 GHz	18.70 - 21.20 GHz
	Transmit	30.00 - 31.00 GHz	29.20 - 31.00 GHz	27.00 - 31.00 GHz
Midband Gain (+/- .5 dB)	Receive	49.40 dBi	49.20 dBi	49.20 dBi
	Transmit	52.60 dBi	52.40 dBi	52.40 dBi
VSWR		1.25:1 max	1.3:1 max	Rx: 1.5:1 max Tx: 1.3:1 max
Pattern Beamwidth (in degrees at midband)	-3 dB	Rx: 0.56° Tx: 0.38°	Rx: 0.57° Tx: 0.39°	Rx: 0.58° Tx: 0.40°
	-15 dB	Rx: 1.26° Tx: 0.86°	Rx: 1.28° Tx: 0.87°	Rx: 1.31° Tx: 0.88°
Sidelobe Envelope, Co-Pol (dBi)				
100λ / D < θ ≤ 20°		29 - 25 Logθ dBi	29 - 25 Logθ dBi	29 - 25 Logθ dBi
20° < θ ≤ 26.3°		-3.5 dBi	-3.5 dBi	-3.5 dBi
26.3° < θ ≤ 48°		32 - 25 Logθ dBi	32 - 25 Logθ dBi	32 - 25 Logθ dBi
θ > 48°		-10 dBi (averaged)	-10 dBi (averaged)	-10 dBi (averaged)
Antenna Noise Temperature				
5° Elevation		162 K	162 K	165 K
10° Elevation		131 K	131 K	134 K
20° Elevation		108 K	108 K	111 K
40° Elevation		94 K	94 K	97 K
Power Handling		100 W	100 W	100 W
Cross Polarization Isolation				
On Axis		24.80 dB	Rx: 17.70 dB Tx: 21.30 dB	Rx: 30.00 dB Tx: 35.00 dB
Within 1.0 dB Beamwidth		24.80 dB	Rx: 17.70 dB Tx: 21.30 dB	26 dB
Output Waveguide Interface Flange		Rx: WR42 Tx: WR28	Rx: WR42 Tx: WR28	Rx: WR42 Tx: WR28
Mechanical				
Reflector Material		Glass Fiber Reinforced Polyester SMC, Ka-Band Formulation		
Antenna Optics		Prime Focus, Offset Feed		
Mast Pipe Size		5.0" SCH 40 Pipe (5.56" OD) 14.1 cm		
Elevation Adjustment Range		5° to 90°, Continuous Fine Adjustment		
Azimuth Adjustment Range		+ 10° Fine Adjustment, 360° Continuous		
Shipping Specifications		295 lbs. (134 kg.)		
Environmental Performance				
Wind Loading	Operational	50 mph (80 km/h)		
	Survival	125 mph (201 km/h)		
Temperature (operational)		- 40° to 140°F (- 40° to 60°C)		
Rain (operational)		½" / hr		
Atmospheric Conditions		Salt, Pollutants and Contaminants as Encountered in Coastal and Industrial Areas		
Solar Radiation		360 BTU/h/ft ²		

GENERAL DYNAMICS SATCOM Technologies

Authorized Distributor: Servsat Communications, Inc. • Atlanta, GA 30005 USA • Telephone: +1-757-1767 •

1000-028 Rev. 02/12

Email: sales@servsat.com • Web Site: www.servsat.com

© 2012 General Dynamics. All rights reserved. General Dynamics reserves the right to make changes in its products and specifications at anytime and without notice. All trademarks indicated as such herein are trademarks of General Dynamics. All other product and service names are the property of their respective owners. © Reg. U.S. Pat. and Tm. Off.