

UT-4505/X C-Band Up Converter



APPLICATION

The Comtech EF Data (CEFD) UT-4505/X Up Converter is the ultimate in high performance and cost effective C-Band frequency conversion. The UT-4505/X can be used for SCPC, DAMA, and TDMA, as well as full transponder HDTV and analog TV. Spectral purity and stability characteristics fully meet or exceed the requirements of all domestic, international, and regional commercial satellite networks.

HIGH GAIN

The UT-4505/X has +17 dBm minimum output level at the 1 dB compression point and 35 dB of gain as a standard. These standard capabilities permits longer cable runs to the high power amplifier or compensates for elaborate combining networks without adding expensive options such as external line amplifiers.

LOW PHASE NOISE

The phase noise performance of the UT-4505/X exceeds the Intelsat phase noise mask for IBS and IDR services by more than 9 dB. This allows phase dependent demodulators to perform better. The close-in phase noise is very low, making the converter ideal for low bit rate digital circuits such as those used in DAMA hub earth stations.

REMOTE CONTROL

The remote control interface is selectable between EIA-232 and EIA-485. All configuration control, status retrieval, and adjustments are available as simple ASCII commands through the serial interface or through the front panel menu. As a cost option, the remote control command structure can be customized in order to accommodate existing network control software.

DETACHABLE I/O MODULE

Each UT-4505/X is equipped with a detachable I/O Module (IOM) that establishes input and output connection types. The module inserts into a rear compartment of the converter, and requires no additional outside space. The IOM includes a Type N connector for the RF path and a BNC connector at 50 or 75Ω for the IF path.

DAISY CHAIN REDUNDANCY SWITCHING

The converter uses CEFD's proprietary "Daisy Chain" integrated switching technology. The Daisy Chain design removes the relays associated with a centralized protection switch tray and distributes them across the individual converters. CEFD was awarded patent 5,666,646 on this distributed protection switch topology.

Daisy Chain technology successfully eliminates a central switching chassis, two power supplies, a microprocessor, and several long, costly cables. Widely accepted in the industry, CEFD's Daisy Chain provides both pricing and marketing advantages.

MINIMUM RACK SPACE

Due to its small rack height (1.75 inches) and the elimination of the space penalty paid for a separate 1+N switch chassis, the UT-4505/X and the Daisy Chain switch architecture provide the most compact and cost effective converter subsystem available. The units are ideal for the construction of transportable systems such as "flyaways," and high capacity earth stations where space utilization and economy are prime considerations.

UT-4505/X C-Band Up Converter

Specifications

Frequency Range

UT-4505	5845 to 6425 MHz
UT-4505/E	6725 to 7025 MHz
UT-4505/F	6425 to 6725 MHz
UT-4505/G	5925 to 6725 MHz
UT-4505/H	5850 to 6650 MHz
UT-4505/J	7025 to 7075 MHz

Conversion

Dual, No Inversion

Step Size

125 kHz standard, 1 kHz optional

Preset Channels

32 frequencies and gains

Stability Over Time

$\pm 1 \times 10^{-9}$ /Day

Stability Over Temp

$\pm 1 \times 10^{-8}$ 32 to 122°F (0 to 50°C)

IF Input

Noise Figure

12 dB Maximum at 0 dB Attenuation

Level

-35 dBm Typical

Range

52 to 88 or 104 to 176 MHz

Impedance

50 or 75Ω

Return Loss

23 dB Minimum with IO Module or Switch Module

RF Output

Output Level

+17 dBm at 1 dB Compression

Intermodulation

-50 dBc @ 0 dBm Output SCL

Carrier Mute

-70 dBc

Non-Carrier Spurious

-80 dBm

Carrier Spurious

-65 dBc @ 0 dBm Output

AM to PM

0.1°/dB at -5 dBm Out

Return Loss

20 dB Minimum with I/O Module

Impedance

50Ω

Transfer

Gain

35 dB \pm 2 dB

Attenuation Adjust

0 to 25 in 0.25 dB Steps

0.1 dB Steps Optional

Gain Stability

± 0.25 dB/Day

Ripple

± 0.25 dB (± 18 MHz)

0.75 dB (± 36 MHz)

Slope

0.05 dB/MHz

External Reference

Input, either 5 or 10 MHz Option @

+3 dBm

Optional 10 MHz Rear Panel Reference

Output

Group Delay

Linear

0.03 ns/MHz

Parabolic

0.01 ns/MHz²

Ripple

1.0 ns Peak-to-Peak

Phase Noise	Limit (dBc/Hz)		Typical (dBc/Hz)	
	UT-4505	UT-4505/X	UT-4505	UT-4505/X
100 Hz	-80	-69	-83	-72
1 KHz	-89	-79	-92	-82
10 KHz	-95	-89	-97	-92
100 KHz	-105	-99	-109	-102
1 MHz	-120	-109	-124	-112

Remote Control (Rear Panel)

Comm Port RS-485 or RS-232C

Indicators (Front Panel)

Power On	Green LED
Mute	Yellow LED
Remote	Yellow LED
Reference	Yellow LED
Stored Fault	Red LED
Fault	Red LED

Test Points (Front Panel)

RF Sample	SMA, -20 dBc Nominal
IF Sample	BNC, -20 dBc Nominal
Optional L.O. Sample	

Power

Voltage	90 to 250 VAC Auto ranging, optional -48 VDC
Frequency	47 to 63 Hz
Dissipation	60 Watts

Environmental

Temperature	32 to 122°F (0 to 50°C)
Altitude	10,000 Feet MSL
Humidity	0 to 95% Relative Humidity

Physical

Dimensions (1RU)	19W x 1.75H x 22D Inches (48.30W x 4.45H x 55.90D cm)
Weight	15 Pounds (7.0 kg)

MTBF

49,740 hrs (calculated)
> 100,000 hrs. (field experience)

Summary Alarm

Relay Closure	Form C
---------------	--------

