

**PRODUCT
SPECIFICATIONS**

Detail Photos

(on right from top to bottom)

Pre-assembled Az/EI Mount

Fine-elevation adjustment
with stamped degree scale

RF tested Ku-band feed
assembly



The reflector is thermoset-molded for strength and surface accuracy.



1.2 m RxTx Class I Antenna System

TYPE 120TX

The Skyware Global Type 120TX 1.2 m Class I RxTx Antenna is a rugged commercial grade product suitable for the most demanding applications. The reflector is thermoset-molded for strength and surface accuracy. Molded into the rear of the reflector is a network of support ribs which not only strengthens the antenna, but also helps to sustain the critical parabolic shape necessary for transmit performance.

The Az/EI mount is constructed from heavy-gauge steel to provide a rigid support to the reflector. The Az/EI mount secures the antenna to any 73-76 mm (2.88"-3.00") O.D. mast and prevents slippage in high winds. A specially formulated powder paint process offers excellent protection from weather-related corrosion.

- All materials comply with EU directive No. 2002/95/EC (RoHS).
- One-piece thermoset-molded offset reflector.
- Single bolt fine elevation adjustment.
- Galvanized 19 mm (.75") O.D. feed support legs.
- Factory pre-assembled mount.
- Plated hardware for maximum corrosion resistance.
- Available with C-band or Ku-band feeds.
- Class I system designed for typical 1 W and 2 W Block Up-Converters (BUCs).

*** 2 kg or 4.5 lb max. weight for RF electronics (BUC and LNB) Ku-Band*

5 kg or 11 lb max. weight for RF electronics (BUC and LNB) at C-Band

SPECIFICATIONS

Type 120TX 1.2 m RxTx Class I Antenna System

RF Performance

	C-band	Ku-band
Effective Aperture	1.2 m (48 in)	1.2 m (48 in)
Operating Frequency	Tx ... 5.850 - 6.725 GHz Rx ... 3.400 - 4.200 GHz	13.75 - 14.50 GHz 10.70 - 12.75 GHz
Polarization	Linear, Orthogonal	Linear, Orthogonal
Gain (± 3 dBi)	Tx ... 35.9 dBi @ 6.1 GHz Rx ... 32.0 dBi @ 3.9 GHz	43.3 dBi @ 14.3 GHz 41.8 dBi @ 12.0 GHz
3 dB Beamwidth	Tx ... 2.7° @ 6.1 GHz Rx ... 4.2° @ 3.9 GHz	1.2° @ 14.3 GHz 1.5° @ 12.0 GHz
Sidelobe Envelope (Tx, Co-Pol dBi)		
Mainbeam $< \theta < 20^\circ$	29 - 25 Log θ	29 - 25 Log θ
$20^\circ < \theta < 26.3^\circ$	-3.5	-3.5
$26.3^\circ < \theta < 48^\circ$	32 - 25 Log θ	32 - 25 Log θ
$48^\circ < \theta < 180^\circ$	-10	-10
Antenna Cross-Polarization	30 dB on Axis	30 dB on Axis
Antenna Noise Temperature		
10° El	60° K	45° K
20° El	52° K	37° K
30° El	50° K	34° K
VSWR	Tx ... 1.3:1 Rx ... 1.4:1	1.3:1 1.5:1
Isolation (Port to Port)	Tx ... 60 dB Rx ... 60 dB	80 dB 35 dB
Feed Interface	Tx ... CPR-137 or Type N Rx ... CPR-229	WR75 Flat Flange WR75 Flat Flange

(All specifications typical)

Mechanical Performance

Reflector Material	Glass Fiber Reinforced Polyester
Antenna Optics	One-Piece Offset Feed Prime Focus
Mount Type	Elevation over Azimuth
Elevation Adjustment Range	10° - 90° Continuous Fine Adjustment (0° to 45° Inverted)
Azimuth Adjustment Range	360° Continuous
Mast Pipe Interface	73 - 76 mm (2.88 in - 3.00 in) Diameter
Wind Loading	Operational Survival	80 km/h (50 mph) 200 km/h (125 mph)
Temperature	-50°C to 80°C
Humidity	0 to 100% (Condensing)
Atmosphere	Standard Hardware Meets 500 Hour Salt Spray Test Requirements (ASTM B-117)
Solar Radiation	360 BTU/h/ft ²
Shock and Vibration	As Encountered During Shipping and Handling



All designs, specifications and availabilities of products and services presented in this bulletin are subject to change without notice.

VST-007.2

© 2010 Skyware Global