

# Type 243: 2.4m Receive-Only Antenna System



## PRODUCT SPECIFICATIONS

### Detail Photos

(on right from top to bottom)

Pre-assembled Az/EI Mount

Fine-elevation adjustment with stamped degree scale

Ku feed assembly with LNB cover



## 2.4 m Receive-Only Antenna System

### TYPE 243

The two-piece reflector is thermoset-molded for strength and surface accuracy.

The Skyware Global 2.4 m Type 243 Offset Receive-Only Antenna is a rugged commercial grade product suitable for the most demanding applications. The reflector is thermoset-molded for strength and surface accuracy. Molded into the rear of the reflector is a network of support ribs which not only strengthens the antenna, but also helps to sustain its critical parabolic shape.

The Az/EI mount is constructed from heavy-gauge steel to provide a rigid support to the reflector. The Az/EI mount secures the antenna to any 168 mm (6.63") O.D. mast and prevents slippage in high winds.

A specially formulated powder paint process offers excellent protection from weather-related corrosion

- All materials comply with EU directive No. 2002/95/EC (RoHS).
- One-piece thermoset-molded offset reflector.
- Fine azimuth and elevation adjustments.
- Galvanized 19 mm (.75") O.D. feed support legs.
- Factory pre-assembled Az/EI mount.
- Plated hardware for maximum corrosion resistance.
- Available with C-band or Ku-band feeds.



Satcom solutions for the long haul

REV 03/15-02  
Page 1 of 2

1315 Outlet Center Drive, Smithfield, NC 27577

All designs, specification and availabilities of products and services presented in this bulletin are subject to change without notice. ©2015 Skyware Global

## • PRODUCT SPECIFICATIONS

### RF Performance

	C-band	Ku-band
Effective Aperture	2.4 m (96 in)	2.4 m (96 in)
Operating Frequency	3.4 - 4.2 GHz	10.70 - 12.75 GHz
Polarization	Linear (Circular Optional)	Linear (Circular Optional)
Gain @ 3.95/11.95 GHz	38.0 dBi	47.6 dBi
3 dB Beamwidth	2.1°	0.7°
Antenna Noise Temperature @ 30° Elevation	36° K	31° K
VSWR*	1.4:1	1.3:1
Antenna Cross Polarization	30 dB on Axis (Linear)	30 dB on Axis (Linear)
Feed Interface	CPR-229	WR75 Flat Flange

(All specifications typical)

\*Function of feed specifications

## 2.4m Receive Only Antenna System

### Mechanical Performance

Reflector Material	Glass Fiber Reinforced Polyester
Antenna Optics	One-Piece Offset Feed Prime Focus
Mount Type	Elevation over Azimuth
Elevation Adjustment Range	10° - 90° Continuous Fine Adjustment
Azimuth Adjustment Range	360° Continuous ± 12° Fine Adjustment
Mast Pipe Interface	168 mm (6.63 in) Diameter
Wind Loading	Operational .80 km/h (50 mph) Survival 200 km/h (125 mph)
Temperature	-50°C to 80°C
Humidity	0 to 100% (Condensing)
Atmosphere	Standard Hardware Meets 500 Hour Salt Spray Test Requirements (ASTM B-117)
Solar Radiation	360 BTU/h/ft <sup>2</sup>
Shock and Vibration	As Encountered During Shipping and Handling



REV 03/15-02  
Page 2 of 2



Satcom solutions for the long haul

1315 Outlet Center Drive, Smithfield, NC 27577

All designs, specification and availabilities of products and services presented in this bulletin are subject to change without notice. ©2015 Skyware Global